

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number
WO 2005/058706 A1

(51) International Patent Classification⁷: **B65B 61/28**,
43/46, B65G 47/91

(21) International Application Number:
PCT/NL2004/000882

(22) International Filing Date:
17 December 2004 (17.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1025061 18 December 2003 (18.12.2003) NL

(71) Applicant (for all designated States except US): **FRIES-
LAND BRANDS B. V.** [NL/NL]; Blankenstein 142,
NL-7943 PE Meppel (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **VERHOEVEN, An-
tonius, Jacobus, Maria** [NL/NL]; Bosch 54, NL-6021 AP
Budel (NL).


(74) Agents: **VAN WESTENBRUGGE, Andries et al.**; Ned-
erlandsch Octrooibureau, Scheveningseweg 82, P.O. Box
29720, NL-2502 LS The Hague (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DEVICE FOR GRIPPING A FLEXIBLE CONTAINER



(57) Abstract: A device for gripping a flexible container, such as a bag filled with fluid, comprising a chamber that is open on one side with a peripheral wall that encloses the open side, a container support that extends in the peripheral direction inside the peripheral wall, as well as an orifice for connecting a vacuum source to the chamber, wherein the chamber can be placed with the open side against the container, such that a vacuum can be generated between the chamber and the container for bringing the container in to contact around the container support transversely to the peripheral direction. The orifice is outside the container support and extends in the peripheral direction.

WO 2005/058706 A1

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.